

Specification

M2Desk-Flex FLF



Product number	M2Desk-Flex	M2Desk-Flex Pro
CPU	Intel® Quad-core, up to 2,16 GHz, Cache 2048KB	Intel® Quad-core, up to 2,41 GHz, Cache 2048KB
Graphics	Intel Gen7 Graphics DX11 Basic 313MHz Dynamic 854MHz	Intel Gen7 Graphics DX11 Basic 688MHz Dynamic 854MHz
RAM	Max. 8GB (2x 4Gb) ULV Dual Channel DDR3 1333	Max. 8GB (2x 4Gb) ULV Dual Channel DDR3 1333
Power Consumption unit	8 - 19 Watt depending on installed options	11 - 21 Watt depending on installed options
LCD Size	Display 15,6" LED TFT 1366 x 768	
Network	Realtek GbE LAN 10/100/1000	
Audio	Realtek High Definition Audio	
Ports	1x USB 2.0 connector (integrated in Display Unit) 0,5A	
	1x Audio/mic 3,5mm jack	
Connectivity-box	2x USB 2.0 1x RJ45	
	M2Desk PoE IEEE.802.3at (Powered through M2Desk SpC-System) or DC power 8-19 V	
SSD	SSD MSata 60 Gb. Optional 120Gb / 240 / 480 Gb	
Camera Module	UXGA 1620 X 1220 and supports 720p30 HD video (30 frames per second)	
Touch screen (optional)	Optional Second generation Capacitive Multi Touch Screen with palm suppression / Write-Touch Screen	
Keyboard	M2Desk , RF-6490-BK, US layout Wireless or wired	
Dimensions unit	W55,5cm x D42,6cm x H4,8cm	
Supported operating system	M2Desk-FLE supports Windows 7 / 8 / 8.1 and 10 (32/64bits)	
Delivered operating system	Free DOS	
Guarantee	For the Dutch markets: Two year hardware components first year Carry-in warranty. One year on mechanics. Upgradeable to 3 years Carry-in, 3 years NBD On-side or 3 years SBD On-side.	
Operation Temperature (°C)	0°C - 40°C	
Storage Temperature (°C)	0°C - 50°C	
Color M2Desk-Flex unit	Black & white	
Weight	approx. 11 Kg	